


NTN BEARING CORPORATION OF AMERICA

Head Office

1600 E. Bishop Court, P.O. Box 7604

Mount Prospect, IL 60056-7604, U.S.A.


Phone: 847-298-7500

Fax: 847-699-9744

Toll Free: 800-323-2358

Email: mkt@ntnamerica.com
Website: www.ntnamericas.com

Item # 6201LLU, Single Row Radial Ball Bearing - Double Sealed (Contact Rubber Seal)


[Order Now](#) | [Technical Specifications](#) | [Dimensional Specifications](#)

Order Now

Ordering Options

[FIND A DISTRIBUTOR](#)
[CONTACT NTN CUSTOMER SUPPORT SPECIALIST](#)
[ORDER THROUGH NTN DOL \(AUTHORIZED DISTRIBUTORS ONLY\)](#)

Technical Specifications


Type

Deep Groove Ball Bearing

Bore Type	Round
Material	High Carbon Chrome Steel
Cage Type	Pressed
Cage Material	Steel
Ball Material	Steel
Limiting Speed - Grease	16000 RPM
Seal Type	Contact
Seal Material	Nitrile Rubber
Precision	ISO Class 0
Configuration	One
Factor	12.7
Radial Internal Clearance	CN
Static Load Rating	620 lbf 2750 N 2.75 kN
Dynamic Load Rating	1510 lbf 6750 N 6.75 kN
Enclosure	Double Sealed
Weight	0.082 lb 0.037 kg
Operating Temperature Range	-40 to 250 °F -40 to 120 °C

Dimensional Specifications





Single Row Radial Ball Bearing - Double Sealed (Contact Rubber Seal) - Dimensions

d	0.4724 in 12.000 mm
D	1.2598 in 32.000 mm
B	0.3937 in 10.000 mm
r	0.0236 in 0.600 mm
r1	0.0197 in 0.500 mm
da max	0.6693 in 17.000 mm
Da max	1.1024 in 28.000 mm
ras max	0.0236 in 0.600 mm